

Blue Dye AHF

An oil soluble blue dye for use in the identification of hydraulic system leaks. At the recommended treat rate, this dye is expected to produce blue coloring in petroleum fluids.

Directions:

- Shake well before using
- Add slowly to system
- Allow sufficient time for dye to be thoroughly dispersed
- Do not add an excessive amount
- ADD 4 Ounces per 100 Gallons

Caution!

Causes eye and skin irritation. Avoid contact

First Aid: eyes, skin, or clothing. Wash thoroughly after handling.

In case of contact with eyes, wash for 10-15

minutes. If ingested, DO NOT INDUCE

VOMITING

GET MEDICAL ATTENTION AS SOON AS

Sandy Brae Laboratories

119A Sandy Drive

Newark, De 19713 USA

tel: 302-456-0446 fax: 302-456-0441

office@sandybrae.com, www.sandybrae.com

Green Dye 2BHF

An oil soluble green dye for use in the identification of hydraulic system leaks. At the recommended treat rate, this dye is expected to produce green coloring in petroleum fluids.

Directions:

- Shake well before using
- Add slowly to system
- Allow sufficient time for dye to be thoroughly dispersed
- Do not add an excessive amount
- ADD 4 Ounces per 100 Gallons

Caution!

Causes eye and skin irritation. Avoid contact with

First Aid: eyes, skin, or clothing. Wash thoroughly after handling.

In case of contact with eyes, wash for 10-15

minutes. If ingested, DO NOT INDUCE

VOMITING

GET MEDICAL ATTENTION AS SOON AS

POSSIBLE. Sandy Brae Laboratories

119A Sandy Drive

Newark, De 19713 USA

Contains: Petroleum Hydrocarbon 58% C.A.S. 64742-94-5

tel: 302-456-0446 fax: 302-456-0441

office@sandybrae.com, www.sandybrae.com

BHF Red Dye

An oil soluble red dye for use in the identification of hydraulic system leaks. At the recommended treat rate, this dye is expected to produce red coloring in petroleum fluids.

Part #: 01-DYE-RED 1 Pint

Directions:

- Shake well before using
- Add slowly to system
- Allow sufficient time for dye to be thoroughly dispersed
- Do not add an excessive amount
- Recommended treat is 3 fluid ounces per 100 gallons

Precautionary Information:

Caution! Contains azo dyes. Causes eye and skin irritation. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

First Aid: In case of contact, immediately flush eyes or skin with plenty of water. Call a physician if irritation persists. Remove contaminated clothing and wash before reuse. Refer to Material Safety Data Bulletin for further safety and handling information.

Contains: Petroleum Hydrocarbon 58% C.A.S. 64742-53-6
C.I. Solvent Red 164 42% 2-Naphthalenol (Phenylazo)
Phenyl Azo Alkyl Derivative. TSCA Accession # 35371
For Emergencies call:

INFOTRAC: 1-800-535-5053

Sandy Brae Laboratories

119A Sandy Drive Newark, DE 19713 USA

Tel: 302-456-0446 Fax: 302-456-0441

Email: office@sandybrae.com Web: www.sandybrae.com

Purple Dye

An oil soluble purple dye for use in the identification of hydraulic system leaks. At the recommended treat rate, this dye is expected to produce blue coloring in petroleum fluids.

Directions:

- Shake well before using
- Add slowly to system
- Allow sufficient time for dye to be thoroughly dispersed
- Do not add an excessive amount
- ADD 4 Ounces per 100 Gallons

Caution!

Causes eye and skin irritation. Avoid contact with eyes, skin, or clothing. Wash thoroughly after handling.

First Aid

In case of contact with eyes, wash for 10-15 minutes. If ingested, DO NOT INDUCE VOMITING,

Contains: Petroleum Hydrocarbon 54% C.A.S. 64742-94-5
Naphthalene 0.5% C.A.S. 91-20-3. Colorant:
25%

Proprietary: 21% C.I. Solvent Red 164 TSCA #
35371

Sandy Brae Laboratories

119A Sandy Drive Newark, DE 19713 USA

Tel: 302-456-0446 Fax: 302-456-0441

Email: office@sandybrae.com Web: www.sandybrae.com

Orange DRHF Dye

An oil soluble **orange dye** for use in the identification of hydraulic system leaks. At the recommended treat rate, this dye is expected to produce **orange** coloring in petroleum fluids. Part#01-DYE-ORANGE

Directions:

- ▲ Shake well before using
- ▲ Add slowly to system
- ▲ Allow sufficient time for dye to be thoroughly dispersed
- ▲ Do not add an excessive amount
- ▲ ADD **4 Ounces per 100 Gallons**

Caution! Causes eye and skin irritation. Avoid contact with eyes, skin, or clothing. Wash thoroughly After handling.

First Aid: In case of contact with eyes, wash for 10-15 minutes. If ingested, DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION AS SOON AS POSSIBLE.

Contains: Petroleum Hydrocarbon 48% C.A.S. 64742-94-5

Naphthalene 0.4% C.A.S. 91-20-3

Sandy Brae Laboratories

3 S Tatnall Street, DE 198901 USA

Tel: 302-456-0446 Fax: 302-456-0441

Email: office @ sandybrae.com Web: www.sandybrae.com

Brown 2HF Dye

An oil soluble brown dye for use in the identification of hydraulic system leaks. At the recommended treat rate, this dye is expected to produce brown coloring in petroleum fluids.

Directions:

- Shake well before using
- Add slowly to system
- Allow sufficient time for dye to be thoroughly dispersed
- Do not add an excessive amount
- ADD **1 Ounce per 100 Gallons**

Caution!

Causes eye and skin irritation. Avoid contact with eyes, skin, or clothing.

First Aid: Wash thoroughly after handling.

If ingested, DO NOT INDUCE VOMITING GET MEDICAL ATTENTION AS SOON AS POSSIBLE.

Sandy Brae Laboratories

3 S Tatnall Street, DE 198901 USA

Tel: 302-456-0446 Fax: 302-456-0441

Email: office @ sandybrae.com Web: www.sandybrae.com

Blue FA3 Dye

An oil soluble **fluorescent blue dye** for use in the identification of hydraulic system leaks. This dye is expected to produce yellow fluorescent effects in petroleum fluids when excited by long wave ultra violet light. Part No. 01-DYE-YLWF6-PT

Directions:

- ▲ Shake well before using
- ▲ Add slowly to system
- ▲ Allow sufficient time for dye to be thoroughly dispersed
- ▲ Do not add an excessive amount
- ▲ ADD **7 Ounces per 100 Gallons**

Caution! Causes eye and skin irritation. Avoid contact with eyes, skin, or clothing. Wash thoroughly After handling.

First Aid: In case of contact with eyes, wash for 10-15 minutes. If ingested, DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION AS SOON AS POSSIBLE.

Contains: Petroleum Hydrocarbon 72% C.A.S. 64742-94-5

Sandy Brae Laboratories

3 S Tatnall Street, DE 19801 USA

Tel: 302-456-0446 Fax: 302-456-0441

Email: office @ sandybrae.com Web: www.sandybrae.com

Yellow Dye F4

An oil soluble fluorescent yellow dye for use in the identification of hydraulic system leaks. This dye is expected to produce **yellow-green** fluorescent effects in petroleum fluids when excited by long wave ultra violet light. Part # 01-DYE-YLF4-PT

Directions:

- ▲ Shake well before using
- ▲ Add slowly to system
- ▲ Allow sufficient time for dye to be thoroughly dispersed
- ▲ Do not add an excessive amount
- ▲ ADD **7 Ounces per 100 Gallons**

Caution! Causes eye and skin irritation. Avoid contact with eyes, skin, or clothing. Wash thoroughly After handling.

First Aid: In case of contact with eyes, wash for 10-15 minutes. If ingested, DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION AS SOON AS POSSIBLE.

Contains: Hydrocarbon Oil 35% C.A.S. 64742-53-6
Colorant 65% proprietary

Sandy Brae Laboratories

3 S Tatnall Street, DE 198901 USA

Tel: 302-456-0446 Fax: 302-456-0441

Email: office @ sandybrae.com Web: www.sandybrae.com